

# DYNO CAMS

## ANIMAL ENGINE CAMS

ORDER TOLL FREE!

**1-800-676-6636**

**Part No.**  
**AN-001**

**Racer Net**  
**\$81.95**

INTAKE	LOBE PROFILE	EXHAUST	LOBE PROFILE
020	14 BTDC	020	57.3 BBDC
050	1 ATDC	050	43.2 BBDC
100	17 ATDC	100	26 BBDC
150	34 ATDC	150	9.7 BBDC
175	43 ATDC	175	.3 BBDC
200	54 ATDC	200	11.5 ABDC
225	68 ATDC	225	24.8 ABDC
MAX LIFT	.2565 INCH	MAX LIFT	.2565 INCH
225	36.5 BBDC	225	75.1 BTDC
200	22.8 BBDC	200	61.6 BTDC
175	12 BBDC	175	50.2 BTDC
150	2.5 BBDC	150	40.4 BTDC
100	14.7 ABDC	100	24.3 BTDC
050	30.8 ABDC	050	7.1 BTDC
020	47.6 ABDC	020	7 ATDC
IN OPEN	28 BTDC	EX OPEN	71 BBDC
IN CLOSE	65 ABDC	EX CLOSE	20.5 ATDC
APR LASH.	.003 INCH	APR LASH	.003 INCH
IN. C/L	106 ATDC	EX C/L	115 BTDC

**Part No.**  
**AN-MOD1**

**Racer Net**  
**\$103.95**

INTAKE	LOBE PROFILE	EXHAUST	LOBE PROFILE
020	27.7 BTDC	020	63.7 BBDC
050	16 BTDC	050	52 BBDC
100	.4 BTDC	100	36.4 BBDC
150	14.9 ATDC	150	21.1 BBDC
200	31.7 ATDC	200	4.3 BBDC
250	52.1 ATDC	250	16.1 ABDC
300	85.3 ATDC	300	49.3 ABDC
MAX LIFT	.310 INCH	MAX LIFT	.310 INCH
300	49.4 BBDC	300	85.4 BTDC
250	16.2 BBDC	250	52.2 BTDC
200	4.1 BBDC	200	31.9 BTDC
150	20.8 ABDC	150	15.2 BTDC
100	36.0 ABDC	100	0 BTDC
050	51.6 ABDC	050	15.5 ATDC
020	63.3 ABDC	020	31.9 ATDC
IN OPEN	41.9 BTDC	EX OPEN	78.1 BBDC
IN CLOSE	83.3 ABDC	EX CLOSE	46.0 ATDC
APR LASH.	.003 INCH	APR LASH	.003 INCH
IN. C/L	108.0 ATDC	EX C/L	108.1 BTDC
DUR at 50	247.6 DEG	DUR at 50	247.6 DEG
DUR at 200	152.5 DEG	DUR at 200	152.5 DEG


This cam is for WKA Spec Animal Stock Class. This cam will give you 1/2 hp over the stock cam and still meet the tech requirements for this class. This cam is the result of a month of solid R & D and Dyno Testing. This cam produces significant power in the mid and upper power range. RECOMMENDED CLASS: ANIMAL STOCK

The AN-MOD1 is our new release for the 2005 Animal Modified Class. This Cam has a very wide power band and is capable of revving into the 9000+ RPM range. The AN-MOD is easy on the valve train. RECOMMENDED CLASS: WKA Animal Modified

## ANIMAL BREATHER & ANIMAL PULSE FITTING



APAB



APAPF

**Part No.**      **Description**      **Racer Net**

APAB	Animal Breather	\$ 5.95
APAPF	Animal Pulse Fitting	6.95

**Part No.**  
**AN-002**

**Racer Net**  
**\$81.95**

INTAKE	LOBE PROFILE	EXHAUST	LOBE PROFILE
020	13.7 BTDC	020	56.8 BBDC
050	.7 ATDC	050	43 BBDC
100	16.7 ATDC	100	26 BBDC
150	33.6 ATDC	150	9.7 BBDC
175	42.8 ATDC	175	.2 BBDC
200	53.6 ATDC	200	11.4 ABDC
225	67.5 ATDC	225	24.7 ABDC
MAX LIFT	.2565 INCH	MAX LIFT	.2565 INCH
225	36 BBDC	225	74.5 BTDC
200	22.5 BBDC	200	60.8 BTDC
175	11.9 BBDC	175	49.5 BTDC
150	2.2 BBDC	150	39.7 BTDC
100	14.9 ABDC	100	23.5 BTDC
050	31 ABDC	050	6.5 BTDC
020	45.1 ABDC	020	9.4 ATDC
IN OPEN	23.6 BTDC	EX OPEN	65.2 BBDC
IN CLOSE	57.3 ABDC	EX CLOSE	20.9 ATDC
APR LASH.	.003 INCH	APR LASH	.003 INCH
IN. C/L	105.6 ATDC	EX C/L	114.8 BTDC

The AN-002 is WKA Spec Animal Stock Class cam. It has more aggressive ramp rate. This cam is very close to maximum profile specs producing more bottom and mid range. Top end is the same as AN-001. RECOMMENDED CLASS: Stock JR CS

THESE PROFILE READINGS ARE AS READ IN OUR TEST BLOCK AT DYNO CAM  
MANUFACTURING. WE CANNOT AND WILL NOT GUARANTEE THESE READINGS TO BE THE EXACT SAME